ACTIVE 0W20 DPF HYBRID

HYBRID TECHNOLOGY · PREMIUM ENGINE OIL

0W-20

PRODUCT DESCRIPTION

0W-20 is an advanced, fully synthetic motor oil designed to provide extraordinary motor protection and better fuel economy. 0W-20 meets or exceeds the requirements of various car manufacturers and industrial standards and performs better than traditional oils.

APPLICATIONS AND KEY FEATURES

- Fuel economy
- Compatible with SCR systems
- DPF compatible
- Start-stop systems

PERFORMANCE LEVELS AND SPECIFICATIONS

- API SN/ SM/SL / SJ
- API SN PLUS
- API SP
- API CF
- ACEA C5
- BMW: Approval LONGLIFE-17FE+
- CHRYSLER: MS 12145
- ILSAC GF-3
- ILSAC GF-4
- ILSAC GF-6A
- Ford WSS-M2C947-A
- FORD WSS-M2C962-A1
- Ford WSS-M2C947-B1
- Fiat Chrysler Automotive MS-6395
- FIAT: 9.55535-GSX
- JAGUAR-LAND ROVER: STJLR.03.5006
- JAGUAR-LAND ROVER: STJLR.51.5122
- MB: 229.71
- OPEL: OV0401547
- VOLVO:VCC RBS0-2AE
- VW 508 00 509 00, PORSCHE C20

Manufacturer statement: formulated with additives meeting the listed approvals and specifications. Consult the manufacturer for official OEM approval certificates.

TYPICAL PROPERTIES

Property	Unit	Test Method	Typical Value
Density (15°C)	g/cm³	ASTM D4052	**0.855 - 0,89**
Kinematic viscosity (100°C)	mm²/s	ASTM D445	**8.8**
Viscosity index	—	ASTM D2270	**Min. 165**
Flash point	°C	ASTM D92	**Min. 225**
Pour point	°C	ASTM D97	**Max. -48**

The values given are typical values and do not constitute a specification; minor variations may occur between production batches.

PACKAGING

4 L

EYLÜL OTO MADENİ YAĞ SANAYİ TİCARET LTD. ŞTİ. · AYDINLIKEVLER MAH. NAZMİ AKDENİZ CAD. NO:89/2B MİLAS/MUĞLA · Phone 0 507 368 63 20 · E-mail info@eylulticaret.com
Manufactured by: PARKİM GRES ENDÜSTRİYEL YAĞLAR SANAYİ VE TİCARET LTD. ŞTİ. · İnönü Mah., Gebze Plastikçiler OSB, 32. Sk. No: 11, 41400 Gebze / Kocaeli · Phone +90 262 206 01 01

STORAGE AND HANDLING RECOMMENDATIONS

- Store packages with lids tightly closed, in covered areas.
- Do not expose to direct sunlight or heat sources.
- Ambient temperature should not exceed 60°C. Do not stack more than two pallets on top of each other.
- Do not discharge used oil into sewers, soil or water; deliver it to an authorised waste oil collection point.
- Keep out of reach of children.

HEALTH, SAFETY AND ENVIRONMENT

For information on safe use, transport, storage and disposal, refer to the product Safety Data Sheet (SDS / MSDS).

EYLÜL OTO MADENİ YAĞ SANAYİ TİCARET LTD. ŞTİ. · AYDINLIKEVLER MAH. NAZMİ AKDENİZ CAD. NO:89/2B MİLAS/MUĞLA · Phone 0 507 368 63 20 · E-mail info@eylulticaret.com
Manufactured by: PARKİM GRES ENDÜSTRİYEL YAĞLAR SANAYİ VE TİCARET LTD. ŞTİ. · İnönü Mah., Gebze Plastikçiler OSB, 32. Sk. No: 11, 41400 Gebze / Kocaeli · Phone +90 262 206 01 01