ACTIVE ESTER 0W30 DPF

ESTER TECHNOLOGY · PREMIUM ENGINE OIL

0W-30

PRODUCT DESCRIPTION

The latest contribution technology and synthetic fats are the next generation of motor oil, designed specifically for the use of low viscosity and high profitability, providing long-lived and superior engine protection for urban traffic. It safely prevents sediment, reduces the loss of friction and protects the efficiency of the exhaust emissions systems in diesel and gasoline cars.

APPLICATIONS AND KEY FEATURES

- Fuel economy
- Compatible with SCR systems
- DPF compatible
- Start-stop systems

PERFORMANCE LEVELS AND SPECIFICATIONS

- API SN/SL, API CF
- ACEA C2, ACEA C3
- MB-Approval 229.31
- MB-Approval 229.51
- MB-Approval 229.52
- Porsche C30, VW 504 00, VW 507 00

Manufacturer statement: formulated with additives meeting the listed approvals and specifications. Consult the manufacturer for official OEM approval certificates.

TYPICAL PROPERTIES

Property	Unit	Test Method	Typical Value
Density (15°C)	g/cm³	ASTM D4052	**0.855 - 0,89**
Kinematic viscosity (100°C)	mm²/s	ASTM D445	**9.3 - 12.5**
Viscosity index	—	ASTM D2270	**Min. 160**
Flash point	°C	ASTM D92	**Min. 220 ***
Pour point	°C	ASTM D97	**Max. -35**

** Flash point: the manufacturer's TDS and the manufacturer's web page give different values (web: Min. 200); to be confirmed.*
The values given are typical values and do not constitute a specification; minor variations may occur between production batches.

PACKAGING

4 L · 5 L

STORAGE AND HANDLING RECOMMENDATIONS

- Store packages with lids tightly closed, in covered areas.
- Do not expose to direct sunlight or heat sources.
- Ambient temperature should not exceed 60°C. Do not stack more than two pallets on top of each other.
- Do not discharge used oil into sewers, soil or water; deliver it to an authorised waste oil collection point.
- Keep out of reach of children.

HEALTH, SAFETY AND ENVIRONMENT

For information on safe use, transport, storage and disposal, refer to the product Safety Data Sheet (SDS / MSDS).

EYLÜL OTO MADENİ YAĞ SANAYİ TİCARET LTD. ŞTİ. · AYDINLIKEVLER MAH. NAZMİ AKDENİZ CAD. NO:89/2B MİLAS/MUĞLA · Phone 0 507 368 63 20 · E-mail info@eylulticaret.com
Manufactured by: PARKİM GRES ENDÜSTRİYEL YAĞLAR SANAYİ VE TİCARET LTD. ŞTİ. · İnönü Mah., Gebze Plastikçiler OSB, 32. Sk. No: 11, 41400 Gebze / Kocaeli · Phone +90 262 206 01 01

DRAFT — This document must be verified against manufacturer data before publication, and the SDS must be approved by a competent (certified) Safety Data Sheet preparer.