# ACTIVE 20W50 (API CF-4)

**HIGH MILEAGE TECHNOLOGY · PREMIUM ENGINE OIL**

| | |
|---|---|
| **Preparation date** | 24.10.2026 (draft) |
| **Version** | 00 |
| **Previous version** | — |

*Prepared in accordance with the structure of Annex II of the Turkish KKDİK Regulation (Official Gazette No. 30105, 23.06.2017), equivalent to Annex II of Regulation (EC) No 1907/2006 (REACH).*

## 1 SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

| | |
|---|---|
| **Product name** | ACTIVE 20W50 (API CF-4) |
| **Product type** | Mixture |
| **Packaging** | 20 L |

### 1.2 Relevant identified uses and uses advised against

| | |
|---|---|
| **Identified use** | Multigrade engine oils |
| **Uses advised against** | Do not use the product for purposes other than those specified without consulting the manufacturer. |

### 1.3 Details of the supplier of the safety data sheet

| | |
|---|---|
| **Placed on the market by / brand owner** | EYLÜL OTO MADENİ YAĞ SANAYİ TİCARET LTD. ŞTİ. |
| **Address** | AYDINLIKEVLER MAH. NAZMİ AKDENİZ CAD. NO:89/2B MİLAS/MUĞLA |
| **Phone** | 0 507 368 63 20 |
| **E-mail (person responsible for the SDS)** | info@eylulticaret.com |
| **Manufacturer** | PARKİM GRES ENDÜSTRİYEL YAĞLAR SANAYİ VE TİCARET LTD. ŞTİ. |
| **Manufacturer address** | İnönü Mah., Gebze Plastikçiler OSB, 32. Sk. No: 11, 41400 Gebze / Kocaeli, Türkiye |
| **Phone / Fax** | +90 262 206 01 01 / +90 262 206 01 02 |
| **Manufacturer e-mail** | info@parkim.net |

### 1.4 Emergency telephone number

| | |
|---|---|
| **Emergency** | National Poison Information Centre of Türkiye (UZEM): 114 · General emergency: 112 |
| **Company (office hours)** | 0 507 368 63 20 |

## 2 SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

| | |
|---|---|
| **Physical hazards** | Not classified as hazardous. |
| **Health Hazards** | Not classified as hazardous. |
| **Environmental hazards** | Not classified as hazardous. |

### 2.2 Label elements

| | |
|---|---|
| **GHS pictogram** | Not required (not classified). |
| **Label elements** | There is no label element. |

### 2.3 Other hazards

| | |
|---|---|
| **PBT** | Not applicable. |
| **vPvB** | Not applicable. |

*Note: The DMSO extract test result of this product using the IP 346 method was found to be below 3% (m/m). For this reason, it is exempt from the phrase H350, with reference to 'Annex I entry in 21st ATP'.*

## 3 SECTION 3: Composition / information on ingredients

### 3.2 Mixtures

| Substance name | Cas No. | EC Number | Ratio(%) | symbols | Risk Units |
|---|---|---|---|---|---|
| **Mineral Base Oil** | Mixture | Mixture | 65-95 | — | - |
| **Zinc alkyl dithiophosphate** | 68649-42-3 | 272-028-3 | ≤ 1.6 | N, Xi | R51/53 R36/38R41 |
| **Methacrylate Copolymer** | Registered | — | ≤ 0.1 | Xi | R36 |

*Note: Symbols and R phrases are given in the source SDS according to the former 67/548/EEC (DSD) system; conversion to CLP H statements must be made by the SDS preparer.*

## 4 SECTION 4: First-aid measures

### 4.1 Description of first aid measures

| | |
|---|---|
| **Eye contact** | Hold the eyelids open and rinse the eye with plenty of water for at least 15 minutes. If irritation persists, consult a doctor. |
| **Skin contact** | Wash thoroughly with soap and water. Remove oil-contaminated clothing and rinse the affected area with water. If skin irritation persists, consult a doctor. |
| **Ingestion** | Do not induce vomiting. Rinse the mouth with plenty of water. In case of nausea or other symptoms, consult a doctor and show the product label. |
| **Inhalation** | Move the person to fresh air. If breathing difficulty persists, seek medical attention. |

### 4.2 Most important symptoms and effects, both acute and delayed

| | |
|---|---|
| **Eye contact** | There are no known specific symptoms. |
| **Skin contact** | There are no known specific symptoms. |
| **Ingestion** | There are no known specific symptoms. |
| **Inhalation** | There are no known specific symptoms. |

### 4.3 Immediate medical attention and special treatment

Note to physician: treat symptomatically.

## 5 SECTION 5: Fire-fighting measures

| | |
|---|---|
| **5.1 Extinguishing media** | Suitable extinguishing media: foam, dry chemical powder, carbon dioxide; sand and earth may be used on small fires only. |
| **5.2 Special hazards** | Combustion produces toxic gases. May burn at high temperatures. |
| **5.3 Advice for fire-fighters** | Fires must be extinguished by trained personnel wearing suitable fire-protective clothing and breathing apparatus (oxygen / compressed-air mask). |



**EYLÜL OTO MADENİ YAĞ SANAYİ TİCARET LTD. ŞTİ.** · AYDINLIKEVLER MAH. NAZMİ AKDENİZ CAD. NO:89/2B MİLAS/MUĞLA · Phone 0 507 368 63 20 · E-mail info@eylulticaret.com
**Manufactured by: PARKİM GRES ENDÜSTRİYEL YAĞLAR SANAYİ VE TİCARET LTD. ŞTİ.** · İnönü Mah., Gebze Plastikçiler OSB, 32. Sk. No: 11, 41400 Gebze / Kocaeli · Phone +90 262 206 01 01

## 6 SECTION 6: Accidental release measures

| | |
|---|---|
| **6.1 Personal precautions** | Notify the emergency team. Remove unauthorised persons from the area. Remove open flames that could ignite the spilled product. Where necessary, apply the fire-fighting measures in Section 5. |
| **6.2 Environmental precautions** | Prevent the product from reaching water, sewers and drains; if necessary dig a protective trench and/or build a barrier with dry sand, earth or similar absorbent material. Use floating booms for spills on water. |
| **6.3 Methods for cleaning up** | Absorb the spilled product with absorbent or inert material. Keep waste material and the oil-contaminated surface layer of soil in closed containers in a well-ventilated area. Deliver waste to licensed hazardous waste disposal companies. |
| **6.4 Reference to other sections** | For larger spills contact the 112 emergency call centre. See Section 8 for personal protection and Section 13 for disposal. |

## 7 SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

| | |
|---|---|
| **Safety precautions** | Use the product in well-ventilated areas. Keep away from fire and heat sources. |
| **Safe handling** | Avoid contact with skin and eyes. Do not eat, drink or smoke while handling the product. |

### 7.2 Conditions for safe storage

| | |
|---|---|
| **Suitable conditions** | Storage in bunded or enclosed areas is recommended. Recommended storage temperature: 5°C to 40°C. |
| **Conditions to avoid** | Do not leave in direct sunlight or at high temperature. Avoid contact with water and strong oxidisers. |
| **Packaging material** | Recommended: materials resistant to hydrocarbons. Unsuitable: other materials. |

### 7.3 Specific end uses

Uses specified in Section 1.2.

## 8 SECTION 8: Exposure controls / personal protection

### 8.1 Control parameters

No occupational exposure limit values are given in the source SDS.

### 8.2 Exposure controls

| | |
|---|---|
| **Engineering controls** | Ensure good ventilation. |
| **Respiratory protection** | Not required under normal use. In special cases (e.g. spills) wear a full-face mask; in case of fire use compressed-air breathing apparatus. |
| **Hand protection** | Use gloves resistant to petroleum products, e.g. PVC or neoprene. |
| **Eye protection** | Where necessary use safety glasses with side shields or a face shield. |
| **Skin and body protection** | No special protective clothing required. Avoid skin contact. |
| **Hygiene measures** | Do not eat, drink or smoke while handling. Wash hands before breaks. Remove oil-contaminated clothing and shoes immediately. |
| **Environmental exposure** | Observe the measures in Sections 6 and 7. |



EYLÜL OTO MADENİ YAĞ SANAYİ TİCARET LTD. ŞTİ. · AYDINLIKEVLER MAH. NAZMİ AKDENİZ CAD. NO:89/2B MİLAS/MUĞLA · Phone 0 507 368 63 20 · E-mail info@eylulticaret.com
Manufactured by: PARKİM GRES ENDÜSTRİYEL YAĞLAR SANAYİ VE TİCARET LTD. ŞTİ. · İnönü Mah., Gebze Plastikçiler OSB, 32. Sk. No: 11, 41400 Gebze / Kocaeli · Phone +90 262 206 01 01

## 9 SECTION 9: Physical and chemical properties

| Property | Unit | Value | Test Method |
|---|---|---|---|
| **Appearance** | - | **Amber-Clear** | - |
| **Odour** | - | **Characteristic odour** | - |
| **Odor Threshold** | - | **No data** | - |
| **Pour Point** | °C | **Max. -24** | ASTM D6749 |
| **Flash Point (Open Cup)** | °C | **Min. 230** | ASTM D92 |
| **Density, 15 °C** | g/cm³ | **0.87 - 0.90** | ASTM D4052 |
| **Kinematic Viscosity, 100 °C** | mm²/s | **16.3 - 21.9** | ASTM D445 |

## 10 SECTION 10: Stability and reactivity

| | |
|---|---|
| **Chemical stability** | Stable under normal conditions. |
| **Conditions to avoid** | Excessive heat, high-energy sources that could cause ignition. |
| **Incompatible materials** | Ignition sources, strong oxidisers. |
| **Hazardous decomposition products** | No known hazardous decomposition products under normal conditions. |
| **Contact with water** | No hazardous decomposition products on contact with water. |
| **Formation of unstable products** | No decomposition or formation of unstable products. |

## 11 SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

| | |
|---|---|
| **Eye contact** | Eye contact may cause temporary blindness. |
| **Contact with skin** | Prolonged or repeated contact may cause skin irritation. Contact of the hot product with the skin causes skin burns. |
| **Ingestion** | Harmful if swallowed, may cause poisoning. |
| **Inhalation** | Inhaling mist or smoke may cause irritation of the eyes, nose and throat. The vapor of the hot product is irritating to the upper respiratory tract. |

## 12 SECTION 12: Ecological information

| | |
|---|---|
| **Ecotoxicity** | Harmful to aquatic organisms. Spills form a layer on the water surface and prevent oxygen passage. |
| **Mobility** | Spillages can penetrate the soil and cause ground water contamination. |
| **Persistence and degradability** | It has the ability to accumulate in soil. |

## 13 SECTION 13: Disposal considerations

The product and used product must be recycled or delivered to licensed, authorised organisations for disposal in accordance with applicable waste legislation. Empty packaging may be hazardous because it can contain product residues; drain thoroughly and deliver the packaging to licensed organisations.

## 14 SECTION 14: Transport information

No UN number or transport class is given in the source SDS. As the product is not classified as hazardous (Section 2), it is not regarded as dangerous goods under ADR/RID, IMDG and IATA.



**EYLÜL OTO MADENİ YAĞ SANAYİ TİCARET LTD. ŞTİ.** · AYDINLIKEVLER MAH. NAZMİ AKDENİZ CAD. NO:89/2B MİLAS/MUĞLA · Phone 0 507 368 63 20 · E-mail info@eylulticaret.com
**Manufactured by: PARKİM GRES ENDÜSTRİYEL YAĞLAR SANAYİ VE TİCARET LTD. ŞTİ.** · İnönü Mah., Gebze Plastikçiler OSB, 32. Sk. No: 11, 41400 Gebze / Kocaeli · Phone +90 262 206 01 01

*ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road · RID: Regulations concerning the International Carriage of Dangerous Goods by Rail · IMDG: International Maritime Dangerous Goods Code · IATA: Dangerous Goods Regulations for air transport · MARPOL 73/78: International Convention for the Prevention of Pollution from Ships.*

## 15 SECTION 15: Regulatory information

This safety data sheet has been prepared in the light of the information available at the time of writing. It is the user's responsibility to take all precautions related to the use of the product and to comply with all applicable legislation. The recommendations given are valid when the product is used for the specified applications. Those who supply the product to third parties must pass on the information in this sheet, and employers must explain the risks and precautions described in this sheet to their employees.

### Safety phrases (source SDS)

S2: Keep out of reach of children.
S26: In case of contact with eyes, rinse with plenty of water and seek medical advice.
S29: Do not discharge into drains.
S39: Wear protective glasses/mask.
S46: If swallowed, seek medical advice immediately and show the container or label.

## 16 SECTION 16: Other information

| | |
|---|---|
| **Key data sources** | This Safety Data Sheet has been prepared based on the information received from our raw material suppliers. Product label data. |

### R phrases (Section 3)

R41: Risk of serious eye damage.
R38: Irritating to skin.
R51/53: Toxic to aquatic organisms. It may cause long-term side effects in the water environment.

| | |
|---|---|
| **Prepared by** | _____ |
| **SDS preparer certificate no.** | _____ |
| **Revision date** | _____ |
| **Revision no.** | _____ |

*This safety data sheet has been prepared in the light of the information available at the time of writing.*



**EYLÜL OTO MADENİ YAĞ SANAYİ TİCARET LTD. ŞTİ.** · AYDINLIKEVLER MAH. NAZMİ AKDENİZ CAD. NO:89/2B MİLAS/MUĞLA · Phone 0 507 368 63 20 · E-mail info@eylulticaret.com
**Manufactured by: PARKİM GRES ENDÜSTRİYEL YAĞLAR SANAYİ VE TİCARET LTD. ŞTİ.** · İnönü Mah., Gebze Plastikçiler OSB, 32. Sk. No: 11, 41400 Gebze / Kocaeli · Phone +90 262 206 01 01