ACTIVE 5W30 (ACEA A5/B5)

FUEL ECONOMY TECHNOLOGY · PREMIUM ENGINE OIL

5W-30

PRODUCT DESCRIPTION

A fully synthetic fuel economy engine oil developed for Ford and other manufacturers requiring low HTHS viscosity oils (2.9-3.5 mPa.s). For gasoline and diesel engines calling for an ACEA A5/B5 5W-30 oil; the FORD WSS-M2C913-D specification also covers most engines requiring 913-A, 913-B and 913-C. High soot handling prevents black sludge and viscosity increase, with wear protection when using up to 7% biodiesel (B7). Compatible with catalytic converters and DPF. Consult the vehicle handbook before use.

APPLICATIONS AND KEY FEATURES

- Fuel economy
- DPF compatible
- Compatible with SCR systems
- Start-stop systems

PERFORMANCE LEVELS AND SPECIFICATIONS

- ACEA A5 / B5
- FORD WSS-M2C913-D
- FORD WSS-M2C913-A / -B / -C

Performance levels stated on the product label under “Meets & Exceeds”. Consult the manufacturer for official OEM approval certificates.

TYPICAL PROPERTIES

Property	Unit	Test Method	Typical Value
Density (20°C)	g/cm³	ASTM D1298	**0.851**
Kinematic viscosity (40°C)	mm²/s	ASTM D445	**58.3**
Kinematic viscosity (100°C)	mm²/s	ASTM D445	**10.2**
Viscosity index	—	ASTM D2270	**164**
HTHS viscosity (150°C)	mPa·s	ASTM D4741	**3.1**
Flash point	°C	ASTM D92	**226**
Pour point	°C	ASTM D97	**-42**

The values given are typical values and do not constitute a specification; minor variations may occur between production batches.

PACKAGING

10.5 L

STORAGE AND HANDLING RECOMMENDATIONS

- Store packages with lids tightly closed, in covered areas.
- Do not expose to direct sunlight or heat sources.
- Ambient temperature should not exceed 60°C. Do not stack more than two pallets on top of each other.
- Do not discharge used oil into sewers, soil or water; deliver it to an authorised waste oil collection point.
- Keep out of reach of children.

HEALTH, SAFETY AND ENVIRONMENT

For information on safe use, transport, storage and disposal, refer to the product Safety Data Sheet (SDS / MSDS).

EYLÜL OTO MADENİ YAĞ SANAYİ TİCARET LTD. ŞTİ. · AYDINLIKEVLER MAH. NAZMİ AKDENİZ CAD. NO:89/2B MİLAS/MUĞLA · Phone 0 507 368 63 20 · E-mail info@eylulticaret.com
Manufactured by: PARKİM GRES ENDÜSTRİYEL YAĞLAR SANAYİ VE TİCARET LTD. ŞTİ. · İnönü Mah., Gebze Plastikçiler OSB, 32. Sk. No: 11, 41400 Gebze / Kocaeli · Phone +90 262 206 01 01