ACTIVE ATF-8

SYNTHETIC TRANSMISSION OIL

ATF-8

PRODUCT DESCRIPTION

ACTIVE TRANSMISSION OIL ATF-8 is a fully synthetic fluid for modern automatic transmissions requiring a low viscosity ATF, including ZF 6, 8 and 9-speed gearboxes. For automatic gearboxes, transfer cases and power steering of European, American and Asian vehicles. Reduces friction for fuel economy, with fast cold response, anti-shudder performance, smooth shifting and high shear and oxidation stability. Mix only with similar fluids. Consult the vehicle handbook before use.

APPLICATIONS AND KEY FEATURES

- Automatic transmissions
- 6-9 speed automatic transmissions
- Power steering systems
- Transfer cases
- Anti-shudder performance

PERFORMANCE LEVELS AND SPECIFICATIONS

- ZF LIFEGUARD 8 / 6 / 6 PLUS
- ZF S671 090 312 / 281 / 255
- ZF TE-ML 11
- BMW 83 22 2 152 426 / ATF 3+
- AUDI / VW G 060 162 / G 055 540
- JAGUAR LAND ROVER 02JDE 26444
- LAND ROVER LR023288 / LR023289
- CHRYSLER 68157995AA / 68218925AA
- FIAT 9.55550-AV5
- MB 236.12 / 236.14 / 236.15
- PORSCHE 000 043 304 00
- GM DEXRON VI
- FORD MERCON LV
- AISIN AW-1
- TOYOTA ATF WS

Performance levels stated on the product label under “Meets & Exceeds”. Consult the manufacturer for official OEM approval certificates.

TYPICAL PROPERTIES

Property	Unit	Test Method	Typical Value
Density (20°C)	g/cm³	ASTM D1298	**0.843**
Kinematic viscosity (40°C)	mm²/s	ASTM D445	**30.5**
Kinematic viscosity (100°C)	mm²/s	ASTM D445	**6.1**
Viscosity index	—	ASTM D2270	**152**
Flash point	°C	ASTM D92	**217**

The values given are typical values and do not constitute a specification; minor variations may occur between production batches.

PACKAGING

20 L

STORAGE AND HANDLING RECOMMENDATIONS

- Store packages with lids tightly closed, in covered areas.
- Do not expose to direct sunlight or heat sources.
- Ambient temperature should not exceed 60°C. Do not stack more than two pallets on top of each other.
- Do not discharge used oil into sewers, soil or water; deliver it to an authorised waste oil collection point.
- Keep out of reach of children.

EYLÜL OTO MADENİ YAĞ SANAYİ TİCARET LTD. ŞTİ. · AYDINLIKEVLER MAH. NAZMİ AKDENİZ CAD. NO:89/2B MİLAS/MUĞLA · Phone 0 507 368 63 20 · E-mail info@eylulticaret.com
Manufactured by: PARKİM GRES ENDÜSTRİYEL YAĞLAR SANAYİ VE TİCARET LTD. ŞTİ. · İnönü Mah., Gebze Plastikçiler OSB, 32. Sk. No: 11, 41400 Gebze / Kocaeli · Phone +90 262 206 01 01

HEALTH, SAFETY AND ENVIRONMENT

For information on safe use, transport, storage and disposal, refer to the product Safety Data Sheet (SDS / MSDS).

EYLÜL OTO MADENİ YAĞ SANAYİ TİCARET LTD. ŞTİ. · AYDINLIKEVLER MAH. NAZMİ AKDENİZ CAD. NO:89/2B MİLAS/MUĞLA · Phone 0 507 368 63 20 · E-mail info@eylulticaret.com
Manufactured by: PARKİM GRES ENDÜSTRİYEL YAĞLAR SANAYİ VE TİCARET LTD. ŞTİ. · İnönü Mah., Gebze Plastikçiler OSB, 32. Sk. No: 11, 41400 Gebze / Kocaeli · Phone +90 262 206 01 01