ACTIVE ATF DEXRON III KIRMIZI

DEXRON III TECHNOLOGY · TRANSMISSION OIL

ATF III

PRODUCT DESCRIPTION

ATF III is recommended for many passenger and commercial vehicle automatic transmissions. It provides excellent grip and protection for many years with its zinc-free additive technology that has stable viscosity and significantly reduces friction. It is also suitable for power steering systems, hydraulic applications and some manual transmissions where automatic transmission fluid is specified.

APPLICATIONS AND KEY FEATURES

- Automatic transmissions
- Power steering systems
- Torque converters
- Hydraulic systems

PERFORMANCE LEVELS AND SPECIFICATIONS

- GM Dexron III H
- Ford Mercon
- Allison C4
- Volvo 97341
- TES 389
- MAN 339 Type V1/Z1
- MBApproval 236.1
- MB Approval 236.9
- Voith 55.6335
- ZF TE ML-03D-04D-14A-17C

Manufacturer statement: formulated with additives meeting the listed approvals and specifications. Consult the manufacturer for official OEM approval certificates.

TYPICAL PROPERTIES

Property	Unit	Test Method	Typical Value
Density (15°C)	g/cm³	ASTM D4052	**0.87 - 0,90**
Kinematic viscosity (100°C)	mm²/s	ASTM D445	**7.2 - 9.4**
Viscosity index	—	ASTM D2270	**Min. 150**
Flash point	°C	ASTM D92	**Min. 215**
Pour point	°C	ASTM D97	**Max. -36**

The values given are typical values and do not constitute a specification; minor variations may occur between production batches.

PACKAGING

3 L · **20 L** (on label: ACTIVE OIL DEXRON III RED (ATF-3))

STORAGE AND HANDLING RECOMMENDATIONS

- Store packages with lids tightly closed, in covered areas.
- Do not expose to direct sunlight or heat sources.
- Ambient temperature should not exceed 60°C. Do not stack more than two pallets on top of each other.
- Do not discharge used oil into sewers, soil or water; deliver it to an authorised waste oil collection point.
- Keep out of reach of children.

HEALTH, SAFETY AND ENVIRONMENT

For information on safe use, transport, storage and disposal, refer to the product Safety Data Sheet (SDS / MSDS).

EYLÜL OTO MADENİ YAĞ SANAYİ TİCARET LTD. ŞTİ. · AYDINLIKEVLER MAH. NAZMİ AKDENİZ CAD. NO:89/2B MİLAS/MUĞLA · Phone 0 507 368 63 20 · E-mail info@eylulticaret.com
Manufactured by: PARKİM GRES ENDÜSTRİYEL YAĞLAR SANAYİ VE TİCARET LTD. ŞTİ. · İnönü Mah., Gebze Plastikçiler OSB, 32. Sk. No: 11, 41400 Gebze / Kocaeli · Phone +90 262 206 01 01