ACTIVE BLUE M 10W40

BLUE M TECHNOLOGY · PREMIUM ENGINE OIL

10W-40

PRODUCT DESCRIPTION

It is a low viscosity, high stability engine oil produced as a result of the perfect blend of new generation additives and fully synthetic oils. It is recommended for all kinds of high - performance modern vehicles, passenger cars, multi-point fuel injection gasoline engines, SUVs and Off - roads.

APPLICATIONS AND KEY FEATURES

- Fuel economy
- Gasoline engines
- Diesel engines
- LPG vehicles

PERFORMANCE LEVELS AND SPECIFICATIONS

- API SN
- ACEA A3/B4
- JASO MA2

Manufacturer statement: formulated with additives meeting the listed approvals and specifications. Consult the manufacturer for official OEM approval certificates.

TYPICAL PROPERTIES

Property	Unit	Test Method	Typical Value
Density (15°C)	g/cm³	ASTM D4052	**0.87 - 0,90**
Kinematic viscosity (100°C)	mm²/s	ASTM D445	**12.5 - 16.3**
Viscosity index	—	ASTM D2270	**Min. 135**
Flash point	°C	ASTM D92	**Min. 225**
Pour point	°C	ASTM D97	**Max. -30**

The values given are typical values and do not constitute a specification; minor variations may occur between production batches.

PACKAGING

4 L

STORAGE AND HANDLING RECOMMENDATIONS

- Store packages with lids tightly closed, in covered areas.
- Do not expose to direct sunlight or heat sources.
- Ambient temperature should not exceed 60°C. Do not stack more than two pallets on top of each other.
- Do not discharge used oil into sewers, soil or water; deliver it to an authorised waste oil collection point.
- Keep out of reach of children.

HEALTH, SAFETY AND ENVIRONMENT

For information on safe use, transport, storage and disposal, refer to the product Safety Data Sheet (SDS / MSDS).

EYLÜL OTO MADENİ YAĞ SANAYİ TİCARET LTD. ŞTİ. · AYDINLIKEVLER MAH. NAZMİ AKDENİZ CAD. NO:89/2B MİLAS/MUĞLA · Phone 0 507 368 63 20 · E-mail info@eylulticaret.com
Manufactured by: PARKİM GRES ENDÜSTRİYEL YAĞLAR SANAYİ VE TİCARET LTD. ŞTİ. · İnönü Mah., Gebze Plastikçiler OSB, 32. Sk. No: 11, 41400 Gebze / Kocaeli · Phone +90 262 206 01 01