ACTIVE BLUE M 5W30 DPF

BLUE M TECHNOLOGY · PREMIUM ENGINE OIL

5W-30

PRODUCT DESCRIPTION

A full synthetic engine oil specially developed for higher mileage engines. Its special additives combat the major causes of engine breakdown, such as leakage, deposits, sludge and friction, helping to extend engine life. Seal conditioners keep seals in good condition and help reduce oil consumption. A strong oil film protects against wear under all operating conditions, and instant flow at low temperatures ensures easy cold starts. For petrol, diesel and LPG engines of passenger cars, delivery vans, light trucks, minibuses and campers. Compatible with diesel particulate filters (DPF) and catalytic converters. Consult the vehicle handbook before use.

APPLICATIONS AND KEY FEATURES

- Fuel economy
- Compatible with SCR systems
- DPF compatible
- Start-stop systems

PERFORMANCE LEVELS AND SPECIFICATIONS

- API SN / SM / SL
- API CF
- ACEA C3 / C2
- MB 229.51 / 229.31
- VW 504 00 / 507 00
- PORSCHE C30

Performance levels stated on the product label under “Meets & Exceeds”. Consult the manufacturer for official OEM approval certificates.

TYPICAL PROPERTIES

Property	Unit	Test Method	Typical Value
Kinematic viscosity (100°C)	mm²/s	ASTM D445	**9.3 - 12.5**
Viscosity index	—	ASTM D2270	**Min. 150**
Flash point	°C	ASTM D92	**Min. 210**
Pour point	°C	ASTM D97	**Max. -36**

The values given are typical values and do not constitute a specification; minor variations may occur between production batches.

PACKAGING

4 L · 5 L

STORAGE AND HANDLING RECOMMENDATIONS

- Store packages with lids tightly closed, in covered areas.
- Do not expose to direct sunlight or heat sources.
- Ambient temperature should not exceed 60°C. Do not stack more than two pallets on top of each other.
- Do not discharge used oil into sewers, soil or water; deliver it to an authorised waste oil collection point.
- Keep out of reach of children.

HEALTH, SAFETY AND ENVIRONMENT

For information on safe use, transport, storage and disposal, refer to the product Safety Data Sheet (SDS / MSDS).

EYLÜL OTO MADENİ YAĞ SANAYİ TİCARET LTD. ŞTİ. · AYDINLIKEVLER MAH. NAZMİ AKDENİZ CAD. NO:89/2B MİLAS/MUĞLA · Phone 0 507 368 63 20 · E-mail info@eylulticaret.com
Manufactured by: PARKİM GRES ENDÜSTRİYEL YAĞLAR SANAYİ VE TİCARET LTD. ŞTİ. · İnönü Mah., Gebze Plastikçiler OSB, 32. Sk. No: 11, 41400 Gebze / Kocaeli · Phone +90 262 206 01 01