ACTIVE OIL DEXRON VI RED

SYNTHETIC TRANSMISSION OIL

DEXRON VI

PRODUCT DESCRIPTION

ATF VI is a fully synthetic, high performance, low viscosity transmission oil specially designed for modern automatic transmissions with or without slip locking clutch. It is especially recommended for use in gearboxes, transfer boxes and power steering systems in vehicles of American and Asian automobile manufacturers.

APPLICATIONS AND KEY FEATURES

- Automatic transmissions
- Power steering systems
- Transfer cases
- Anti-shudder performance
- Fuel economy

PERFORMANCE LEVELS AND SPECIFICATIONS

- DEXRON VI/GM DEXRON® VI
- MERCON LV/JASO 1A LV
- Allison C-3 & C-4
- American Motors ATF +3 (MS7176-E)
- Audi 5 HP LT71141 (ZF 5 HP 18FL/19FL/24A)
- Audi/VW G 055 162-A2, A6 (ZF Lifeguardfluid 6 Plus) (ZF No. S671 090 281)
- Audi/VW G 060 162 (ZF Lifeguardfluid 8) (ZF No. S671 090 312)
- BMW LT71141 (ZF 5 HP 18FL/19FL/24A
- BMW MINI/CAT TO-2
- Chrysler/Dodge/Jeep 68171866AA
- FIAT T-IV type , JWS 3309/Ford MERCON®
- Ford WSS M2C 922A1, 924A (XT-8-QAW) JWS 3309
- Ford/Lincoln/ Mercury XT-2-QSM (Syn)
- Ford MERCON® LV (FF-WSS-M2C-938A/SF XT-10 QLV)
- Jaguar WSS-M2C922A1/Jaguar WSS-M2C922A1
- Opel/GM 9986195/Renault Matic D2
- VW G 055 162-A2, A6 (ZF Lifeguardfluid 6 Plus)
- VW G 060 162 (ZF Lifeguardfluid 8)
- VW G US 000 162 /VW TL 521 62
- ZF 9 speed transmissions
- ZF TE-ML 05L /ZF TE-ML 09 /ZF TE-ML 11A 11B /ZF TE-ML 21L

Manufacturer statement: formulated with additives meeting the listed approvals and specifications. Consult the manufacturer for official OEM approval certificates.

TYPICAL PROPERTIES

Property	Unit	Test Method	Typical Value
Density (15°C)	g/cm³	ASTM D4052	**0,85 - 0,875**
Kinematic viscosity (100°C)	mm²/s	ASTM D445	**5.3 - 6.8**
Viscosity index	—	ASTM D2270	**Min. 155**
Flash point	°C	ASTM D92	**Min. 215**
Pour point	°C	ASTM D97	**Max. -38**

The values given are typical values and do not constitute a specification; minor variations may occur between production batches.

PACKAGING

20 L

EYLÜL OTO MADENİ YAĞ SANAYİ TİCARET LTD. ŞTİ. · AYDINLIKEVLER MAH. NAZMİ AKDENİZ CAD. NO:89/2B MİLAS/MUĞLA · Phone 0 507 368 63 20 · E-mail info@eylulticaret.com
Manufactured by: PARKİM GRES ENDÜSTRİYEL YAĞLAR SANAYİ VE TİCARET LTD. ŞTİ. · İnönü Mah., Gebze Plastikçiler OSB, 32. Sk. No: 11, 41400 Gebze / Kocaeli · Phone +90 262 206 01 01

STORAGE AND HANDLING RECOMMENDATIONS

- Store packages with lids tightly closed, in covered areas.
- Do not expose to direct sunlight or heat sources.
- Ambient temperature should not exceed 60°C. Do not stack more than two pallets on top of each other.
- Do not discharge used oil into sewers, soil or water; deliver it to an authorised waste oil collection point.
- Keep out of reach of children.

HEALTH, SAFETY AND ENVIRONMENT

For information on safe use, transport, storage and disposal, refer to the product Safety Data Sheet (SDS / MSDS).

EYLÜL OTO MADENİ YAĞ SANAYİ TİCARET LTD. ŞTİ. · AYDINLIKEVLER MAH. NAZMİ AKDENİZ CAD. NO:89/2B MİLAS/MUĞLA · Phone 0 507 368 63 20 · E-mail info@eylulticaret.com
Manufactured by: PARKİM GRES ENDÜSTRİYEL YAĞLAR SANAYİ VE TİCARET LTD. ŞTİ. · İnönü Mah., Gebze Plastikçiler OSB, 32. Sk. No: 11, 41400 Gebze / Kocaeli · Phone +90 262 206 01 01