ACTIVE ESTER 5W40 DPF

ESTER TECHNOLOGY · PREMIUM ENGINE OIL

5W-40

PRODUCT DESCRIPTION

A fully synthetic engine oil for gasoline and diesel engines complying with Euro 4, 5 and 6 emission standards, naturally aspirated or turbocharged, with direct or indirect injection. Its high HTHS viscosity and Mid SAPS formulation provide a strong oil film in powerful engines, reducing wear and oil consumption. Low ash, phosphorus and sulphur content makes it fully compatible with catalytic converters and diesel particulate filters (DPF). Suitable for all vehicles requiring an ACEA C3 oil. Consult the vehicle handbook before use.

APPLICATIONS AND KEY FEATURES

- Fuel economy
- DPF compatible
- Turbocharged engines

PERFORMANCE LEVELS AND SPECIFICATIONS

- ACEA C3
- API SN
- GM dexos2
- MB 229.51
- PORSCHE A40
- RENAULT RN0700 / RN0710
- BMW LONGLIFE-04 (MY 2018 sonuna kadar)
- VW 505 00 / 505 01
- FORD WSS-M2C917-A
- FIAT 9.55535-GH2 / S2 / T2
- CHRYSLER MS-12991

Performance levels stated on the product label under “Meets & Exceeds”. Consult the manufacturer for official OEM approval certificates.

TYPICAL PROPERTIES

Property	Unit	Test Method	Typical Value
Density (20°C)	g/cm³	ASTM D1298	**0.845**
Kinematic viscosity (40°C)	mm²/s	ASTM D445	**84.7**
Kinematic viscosity (100°C)	mm²/s	ASTM D445	**14.1**
Viscosity index	—	ASTM D2270	**172**
HTHS viscosity (150°C)	mPa·s	ASTM D4741	**3.6**
Flash point	°C	ASTM D92	**234**
Pour point	°C	ASTM D97	**-39**
Total base number (TBN)	mg KOH/g	ASTM D2896	**7.5**

The values given are typical values and do not constitute a specification; minor variations may occur between production batches.

PACKAGING

4 L · 5 L

STORAGE AND HANDLING RECOMMENDATIONS

- Store packages with lids tightly closed, in covered areas.
- Do not expose to direct sunlight or heat sources.
- Ambient temperature should not exceed 60°C. Do not stack more than two pallets on top of each other.
- Do not discharge used oil into sewers, soil or water; deliver it to an authorised waste oil collection point.
- Keep out of reach of children.

EYLÜL OTO MADENİ YAĞ SANAYİ TİCARET LTD. ŞTİ. · AYDINLIKEVLER MAH. NAZMİ AKDENİZ CAD. NO:89/2B MİLAS/MUĞLA · Phone 0 507 368 63 20 · E-mail info@eylulticaret.com
Manufactured by: PARKİM GRES ENDÜSTRİYEL YAĞLAR SANAYİ VE TİCARET LTD. ŞTİ. · İnönü Mah., Gebze Plastikçiler OSB, 32. Sk. No: 11, 41400 Gebze / Kocaeli · Phone +90 262 206 01 01

DRAFT — This document must be verified against manufacturer data before publication, and the SDS must be approved by a competent (certified) Safety Data Sheet preparer.

HEALTH, SAFETY AND ENVIRONMENT

For information on safe use, transport, storage and disposal, refer to the product Safety Data Sheet (SDS / MSDS).

EYLÜL OTO MADENİ YAĞ SANAYİ TİCARET LTD. ŞTİ. · AYDINLIKEVLER MAH. NAZMİ AKDENİZ CAD. NO:89/2B MİLAS/MUĞLA · Phone 0 507 368 63 20 · E-mail info@eylulticaret.com
Manufactured by: PARKİM GRES ENDÜSTRİYEL YAĞLAR SANAYİ VE TİCARET LTD. ŞTİ. · İnönü Mah., Gebze Plastikçiler OSB, 32. Sk. No: 11, 41400 Gebze / Kocaeli · Phone +90 262 206 01 01

DRAFT — This document must be verified against manufacturer data before publication, and the SDS must be approved by a competent (certified) Safety Data Sheet preparer.