ACTIVE GEAR OIL GL-5 75W90

SYNTHETIC GEAR OIL

75W-90

PRODUCT DESCRIPTION

It is a synthetic gear oil formulated from synthetic base oils and an advanced additive system to meet the performance requirements of harsh conditions. It is designed for heavy- duty manual transmissions and rear axles where extreme pressure shock loading is expected, with excellent load carrying capacity over wide operating temperature ranges. This gear oil has excellent thermal and oxidation stability, high Viscosity Index, very low pour point and high fluidity at low temperature.

APPLICATIONS AND KEY FEATURES

- Extreme pressure (EP) protection
- Manual gearboxes
- Hypoid differentials
- Transfer cases

PERFORMANCE LEVELS AND SPECIFICATIONS

- API GL-5/GL-4
- MAN 342 M-1
- MAN 342M-2
- SAE J2360
- Volvo 1273.10
- Scania STO 1:0
- Industrial
- ZF 05A/07A/08/12A/12E/16B-D/17B/19B/21A

Manufacturer statement: formulated with additives meeting the listed approvals and specifications. Consult the manufacturer for official OEM approval certificates.

TYPICAL PROPERTIES

Property	Unit	Test Method	Typical Value
Density (15°C)	g/cm³	ASTM D4052	**0,88 - 0,9**
Kinematic viscosity (100°C)	mm²/s	ASTM D445	**13.5 - 18.5**
Viscosity index	—	ASTM D2270	**Min. 140**
Flash point	°C	ASTM D92	**Min. 200**
Pour point	°C	ASTM D97	**Max. -35**

The values given are typical values and do not constitute a specification; minor variations may occur between production batches.

PACKAGING

20 L

STORAGE AND HANDLING RECOMMENDATIONS

- Store packages with lids tightly closed, in covered areas.
- Do not expose to direct sunlight or heat sources.
- Ambient temperature should not exceed 60°C. Do not stack more than two pallets on top of each other.
- Do not discharge used oil into sewers, soil or water; deliver it to an authorised waste oil collection point.
- Keep out of reach of children.

HEALTH, SAFETY AND ENVIRONMENT

For information on safe use, transport, storage and disposal, refer to the product Safety Data Sheet (SDS / MSDS).

EYLÜL OTO MADENİ YAĞ SANAYİ TİCARET LTD. ŞTİ. · AYDINLIKEVLER MAH. NAZMİ AKDENİZ CAD. NO:89/2B MİLAS/MUĞLA · Phone 0 507 368 63 20 · E-mail info@eylulticaret.com
Manufactured by: PARKİM GRES ENDÜSTRİYEL YAĞLAR SANAYİ VE TİCARET LTD. ŞTİ. · İnönü Mah., Gebze Plastikçiler OSB, 32. Sk. No: 11, 41400 Gebze / Kocaeli · Phone +90 262 206 01 01