ACTIVE MOTOR OIL 10W40

GASOLINE & DIESEL · ENGINE OIL

10W-40

PRODUCT DESCRIPTION

A high-performance synthetic technology engine oil developed for gasoline and diesel passenger cars. For naturally aspirated or turbocharged, direct or indirect injection engines and for diesel engines without a diesel particulate filter (DPF); suitable for gasoline, ethanol, LPG, diesel and biofuels. Its synthetic base stock provides very high lubricating power, reducing friction and volatility, and withstands the very high temperatures reached in modern engines. Anti-oxidation, anti-wear, anti-corrosion and anti-foam properties; compatible with catalytic converters. Consult the vehicle handbook before use.

APPLICATIONS AND KEY FEATURES

- Fuel economy
- Gasoline engines
- Diesel engines
- LPG vehicles

PERFORMANCE LEVELS AND SPECIFICATIONS

- ACEA A3 / B4
- API SERVICE SN / CF
- MERCEDES-BENZ MB 229.3
- RENAULT RN0710 / RN0700
- VW 501 01 / 505 00
- PERFORMANCE: PSA B71 2300

Performance levels stated on the product label under “Meets & Exceeds”. Consult the manufacturer for official OEM approval certificates.

TYPICAL PROPERTIES

Property	Unit	Test Method	Typical Value
Density (20°C)	g/cm³	ASTM D1298	**0.862**
Kinematic viscosity (40°C)	mm²/s	ASTM D445	**102.5**
Kinematic viscosity (100°C)	mm²/s	ASTM D445	**15.0**
Viscosity index	—	ASTM D2270	**153**
Flash point	°C	ASTM D92	**228**
Pour point	°C	ASTM D97	**-36**
Total base number (TBN)	mg KOH/g	ASTM D2896	**10.4**

The values given are typical values and do not constitute a specification; minor variations may occur between production batches.

PACKAGING

4 L · 5 L · 7 L

STORAGE AND HANDLING RECOMMENDATIONS

- Store packages with lids tightly closed, in covered areas.
- Do not expose to direct sunlight or heat sources.
- Ambient temperature should not exceed 60°C. Do not stack more than two pallets on top of each other.
- Do not discharge used oil into sewers, soil or water; deliver it to an authorised waste oil collection point.
- Keep out of reach of children.

HEALTH, SAFETY AND ENVIRONMENT

For information on safe use, transport, storage and disposal, refer to the product Safety Data Sheet (SDS / MSDS).

EYLÜL OTO MADENİ YAĞ SANAYİ TİCARET LTD. ŞTİ. · AYDINLIKEVLER MAH. NAZMİ AKDENİZ CAD. NO:89/2B MİLAS/MUĞLA · Phone 0 507 368 63 20 · E-mail info@eylulticaret.com
Manufactured by: PARKİM GRES ENDÜSTRİYEL YAĞLAR SANAYİ VE TİCARET LTD. ŞTİ. · İnönü Mah., Gebze Plastikçiler OSB, 32. Sk. No: 11, 41400 Gebze / Kocaeli · Phone +90 262 206 01 01