ACTIVE OIL 15W40 CF-4 SJ

HEAVY DUTY TECHNOLOGY · DIESEL ENGINE OIL

15W-40

PRODUCT DESCRIPTION

It is a diesel engine oil reinforced with superior quality base oils and high additives. It is an engine oil that can be used safely in all seasons for automobiles and light commercial vehicles. It is especially suitable for passenger vehicles that operate under difficult conditions and experience frequent stops and starts. It can also be used safely in the lubrication of minibuses, pickup trucks, other four-stroke engines and other work machines. It can also be used safely in vehicles running on fuels such as gasoline and LPG.

APPLICATIONS AND KEY FEATURES

- Diesel engines
- Gasoline engines
- LPG vehicles

PERFORMANCE LEVELS AND SPECIFICATIONS

- API CF-4/CF
- API SJ/SL
- ACEA B2
- ACEA E3/E7
- MB-Onay 228.3
- VOLVO VDS-3
- Cummins CES 20072
- Mack EO-N
- Mack EO-M
- MAN M 3275-1
- RENAULT TRUCKS RD-2
- RENAULT TRUCKS RLD
- Caterpillar ECF-2
- Cummins CES 20077
- Ford WSS-M2C171-D
- Detroit Fluids Şartnamesi93K215

Manufacturer statement: formulated with additives meeting the listed approvals and specifications. Consult the manufacturer for official OEM approval certificates.

TYPICAL PROPERTIES

Property	Unit	Test Method	Typical Value
Density (15°C)	g/cm³	ASTM D4052	**0.87 - 0.90**
Kinematic viscosity (100°C)	mm²/s	ASTM D445	**12.5 - 16.3**
Viscosity index	—	ASTM D2270	**Min. 120**
Flash point	°C	ASTM D92	**Min. 230**
Pour point	°C	ASTM D97	**Max. -24**

The values given are typical values and do not constitute a specification; minor variations may occur between production batches.

PACKAGING

7 L (on label: ACTIVE OIL 15W40) · **20 L**

STORAGE AND HANDLING RECOMMENDATIONS

- Store packages with lids tightly closed, in covered areas.
- Do not expose to direct sunlight or heat sources.
- Ambient temperature should not exceed 60°C. Do not stack more than two pallets on top of each other.
- Do not discharge used oil into sewers, soil or water; deliver it to an authorised waste oil collection point.
- Keep out of reach of children.

EYLÜL OTO MADENİ YAĞ SANAYİ TİCARET LTD. ŞTİ. · AYDINLIKEVLER MAH. NAZMİ AKDENİZ CAD. NO:89/2B MİLAS/MUĞLA · Phone 0 507 368 63 20 · E-mail info@eylulticaret.com
Manufactured by: PARKİM GRES ENDÜSTRİYEL YAĞLAR SANAYİ VE TİCARET LTD. ŞTİ. · İnönü Mah., Gebze Plastikçiler OSB, 32. Sk. No: 11, 41400 Gebze / Kocaeli · Phone +90 262 206 01 01

HEALTH, SAFETY AND ENVIRONMENT

For information on safe use, transport, storage and disposal, refer to the product Safety Data Sheet (SDS / MSDS).

EYLÜL OTO MADENİ YAĞ SANAYİ TİCARET LTD. ŞTİ. · AYDINLIKEVLER MAH. NAZMİ AKDENİZ CAD. NO:89/2B MİLAS/MUĞLA · Phone 0 507 368 63 20 · E-mail info@eylulticaret.com
Manufactured by: PARKİM GRES ENDÜSTRİYEL YAĞLAR SANAYİ VE TİCARET LTD. ŞTİ. · İnönü Mah., Gebze Plastikçiler OSB, 32. Sk. No: 11, 41400 Gebze / Kocaeli · Phone +90 262 206 01 01