ACTIVE ATF-6 SARI

SYNTHETIC TRANSMISSION OIL

ATF-6

PRODUCT DESCRIPTION

ACTIVE TRANSMISSION OIL ATF-6 is a synthetic technology automatic transmission fluid for most modern automatic gearboxes (manual/sequential mode, electronically controlled) and power steering systems. For ZF 5 and 6-speed gearboxes and systems requiring GM DEXRON III and many other manufacturer specifications. Reduces friction for fuel economy, with anti-shudder performance, smooth shifting, fast cold response and high shear and oxidation stability. Consult the vehicle handbook before use.

APPLICATIONS AND KEY FEATURES

- Automatic transmissions
- 5-6 speed automatic transmissions
- Power steering systems
- Anti-shudder performance

PERFORMANCE LEVELS AND SPECIFICATIONS

- GM DEXRON III H / III G / II D
- FORD MERCON V / MERCON
- ALLISON C-4 / TES-295
- ZF LIFEGUARD 5 / 6
- ZF S671 090 170 / 255
- ZF TE-ML 03D / 04D / 09 / 14A / 16L / 17C
- MB 236.1 / 236.5 / 236.7 / 236.9 / 236.10 / 236.12
- BMW ATF2 / ETL 7045E / ETL 8072B / LA2634
- VW / AUDI G 052 025 / G 052 162 / G 052 990
- TOYOTA ATF T-IV / WS / JWS 3309
- HONDA ATF Z1 / DW-1
- HYUNDAI / KIA SP-III
- NISSAN MATIC D / J / K / S
- MITSUBISHI SP-III / ATF-J2 / J3
- CHRYSLER ATF+3 / ATF+4
- VOITH G607
- VOLVO 97340 / 97342

Performance levels stated on the product label under “Meets & Exceeds”. Consult the manufacturer for official OEM approval certificates.

TYPICAL PROPERTIES

Property	Unit	Test Method	Typical Value
Density (20°C)	g/cm³	ASTM D1298	**0.845**
Kinematic viscosity (40°C)	mm²/s	ASTM D445	**36.2**
Kinematic viscosity (100°C)	mm²/s	ASTM D445	**7.6**
Viscosity index	—	ASTM D2270	**185**
Flash point	°C	ASTM D92	**218**

The values given are typical values and do not constitute a specification; minor variations may occur between production batches.

PACKAGING

20 L

STORAGE AND HANDLING RECOMMENDATIONS

- Store packages with lids tightly closed, in covered areas.
- Do not expose to direct sunlight or heat sources.
- Ambient temperature should not exceed 60°C. Do not stack more than two pallets on top of each other.
- Do not discharge used oil into sewers, soil or water; deliver it to an authorised waste oil collection point.
- Keep out of reach of children.

EYLÜL OTO MADENİ YAĞ SANAYİ TİCARET LTD. ŞTİ. · AYDINLIKEVLER MAH. NAZMİ AKDENİZ CAD. NO:89/2B MİLAS/MUĞLA · Phone 0 507 368 63 20 · E-mail info@eylulticaret.com
Manufactured by: PARKİM GRES ENDÜSTRİYEL YAĞLAR SANAYİ VE TİCARET LTD. ŞTİ. · İnönü Mah., Gebze Plastikçiler OSB, 32. Sk. No: 11, 41400 Gebze / Kocaeli · Phone +90 262 206 01 01

HEALTH, SAFETY AND ENVIRONMENT

For information on safe use, transport, storage and disposal, refer to the product Safety Data Sheet (SDS / MSDS).

EYLÜL OTO MADENİ YAĞ SANAYİ TİCARET LTD. ŞTİ. · AYDINLIKEVLER MAH. NAZMİ AKDENİZ CAD. NO:89/2B MİLAS/MUĞLA · Phone 0 507 368 63 20 · E-mail info@eylulticaret.com
Manufactured by: PARKİM GRES ENDÜSTRİYEL YAĞLAR SANAYİ VE TİCARET LTD. ŞTİ. · İnönü Mah., Gebze Plastikçiler OSB, 32. Sk. No: 11, 41400 Gebze / Kocaeli · Phone +90 262 206 01 01