ACTIVE CVT YELLOW

SYNTHETIC CVT TRANSMISSION OIL

CVT YELLOW

PRODUCT DESCRIPTION

It is a high performance transmission fluid specially designed for Continuously Variable Transmission (CVT) gearbox type. Designed for use in a wide range of vehicles with CVT transmissions using chain-pulley or belt-pulley. Not recommended for hybrid vehicles suitable for CVT devices. Always refer to the vehicle's owner's manual or manual before use.

APPLICATIONS AND KEY FEATURES

- CVT transmissions
- Belt and chain type CVT
- Anti-shudder performance
- Fuel economy

PERFORMANCE LEVELS AND SPECIFICATIONS

- Audi Multitronic - BMW Mini Cooper EZL 799/799A
- Daihatsu AMMIX CVTF DFE
- Daihatsu AMMIX CVT Fluid DC- Daihatsu AMMIX CVT
- Fluid DFC- Daihatsu Fluid TC
- Dodge/Jeep/ ChryslerNS Dodge/Chrysler/Jeep/ Mopar
- CVT+ 4 - GM/ Saturn DEX-CVT
- Honda HMMF (without starting clutch) - Honda HCF2- Honda Z-1 (CVT model, without starting clutch , not
- SFU for 2001-2007 Honda Fit & Jazz)- Hyundai/Kia CVT-J 1 - Hyundai/Kia SP III (CVT model)- Idemitsu CVTS-EX1 - Mazda JWS 3320
- Mini Cooper EZL 799/EZL 799A/ZF CVT V 1 -Mitsubishi CVTF-J1 (MMC Diaqueen CVT Fluid J1)
- Mitsubishi CVTF-J4 and -J4+ (MMC Diaqueen CVT Fluid
- J4 and J4+)
- Mitsubishi (Diaqueen) SP-III (CVT model only) -Nissan NS-1, 2, 3 - Punch CVT - Shell Green 1V
- Subaru iCVT - Subaru iCVT FG - Subaru ECVT - Subaru
- Lineartronic chain CVT and CVT II Fluid
- Subaru Lineartronic High Torque (HT) CVT Fluid -Subaru NS-2 - Suzuki CVTF TC - Suzuki CVTF 3320
- Suzuki NS- 2 - Suzuki CVT Green 1 & 2 - Suzuki CVT
- Green 1V - Toyota CVTF TC - Toyota CVTF FE
- VW/Audi TL 521 16 (G 052 516) - VW/Audi TL 521 80 (G 052 180 A2)

Manufacturer statement: formulated with additives meeting the listed approvals and specifications. Consult the manufacturer for official OEM approval certificates.

TYPICAL PROPERTIES

Property	Unit	Test Method	Typical Value
Density (15°C)	g/cm³	ASTM D4052	**0,85 - 0,88**
Kinematic viscosity (100°C)	mm²/s	ASTM D445	**7.2 - 9.4**
Viscosity index	—	ASTM D2270	**Min. 170**
Flash point	°C	ASTM D92	**Min. 200**
Pour point	°C	ASTM D97	**Max. -42**

The values given are typical values and do not constitute a specification; minor variations may occur between production batches.

PACKAGING

20 L

EYLÜL OTO MADENİ YAĞ SANAYİ TİCARET LTD. ŞTİ. · AYDINLIKEVLER MAH. NAZMİ AKDENİZ CAD. NO:89/2B MİLAS/MUĞLA · Phone 0 507 368 63 20 · E-mail info@eylulticaret.com
Manufactured by: PARKİM GRES ENDÜSTRİYEL YAĞLAR SANAYİ VE TİCARET LTD. ŞTİ. · İnönü Mah., Gebze Plastikçiler OSB, 32. Sk. No: 11, 41400 Gebze / Kocaeli · Phone +90 262 206 01 01

STORAGE AND HANDLING RECOMMENDATIONS

- Store packages with lids tightly closed, in covered areas.
- Do not expose to direct sunlight or heat sources.
- Ambient temperature should not exceed 60°C. Do not stack more than two pallets on top of each other.
- Do not discharge used oil into sewers, soil or water; deliver it to an authorised waste oil collection point.
- Keep out of reach of children.

HEALTH, SAFETY AND ENVIRONMENT

For information on safe use, transport, storage and disposal, refer to the product Safety Data Sheet (SDS / MSDS).

EYLÜL OTO MADENİ YAĞ SANAYİ TİCARET LTD. ŞTİ. · AYDINLIKEVLER MAH. NAZMİ AKDENİZ CAD. NO:89/2B MİLAS/MUĞLA · Phone 0 507 368 63 20 · E-mail info@eylulticaret.com
Manufactured by: PARKİM GRES ENDÜSTRİYEL YAĞLAR SANAYİ VE TİCARET LTD. ŞTİ. · İnönü Mah., Gebze Plastikçiler OSB, 32. Sk. No: 11, 41400 Gebze / Kocaeli · Phone +90 262 206 01 01