ACTIVE DSG-DCTF

SYNTHETIC TRANSMISSION OIL

DSG-DCTF

PRODUCT DESCRIPTION

High performance Synthetic lubricant specifically designed for the Dual Clutch Transmission (DCT) transmission type. Suitable for use in a wide range of vehicles equipped with Dual Dry Clutch Transmission and DCT transmissions with Dual Wet Clutch. Also suitable for some mechanical gearboxes that require very low viscosity grade gear oil such as DCTF SAE 75W

APPLICATIONS AND KEY FEATURES

- Dual clutch transmissions (DCT)
- Dry and wet clutch types
- DSG gearboxes
- Anti-shudder performance
- Fuel economy

PERFORMANCE LEVELS AND SPECIFICATIONS

- API GL-4
- VW G 052 529
- MB 236.24
- BMW Drivelogic 7-speed (Getrag)/DCTF-1
- BMW 6-speed DCT
- BMW MTF LT-5
- Chrysler Powershift 6-speed (Getrag)
- DCT-1 SFU Ferrari 7-speed (Getrag)/TE DCT-3
- Ford/Nissan Powershift 6-speed (GFT)
- Ford WSS-M2C936A
- Ford WSS-M2C200-D2/ XT-11-QDC
- Pentosine FFL 4
- Peugeot/CitroenDCS6-speed (GFT)/97343.S2
- Renault EDC 6-speed (Getrag)
- Volvo Powershift 6-speed (GFT)/1161838/1161839
- VW (Audi, Seat , Skoda) 6-speed
- VW/Audi TL 52529 (spec) / G 052 529 A2 or A6 (fluid)
- VW/Audi TL 521 82 (spec) / G 052 182 A2 or A6 (fluid)
- ZF/Porsche Oil

Manufacturer statement: formulated with additives meeting the listed approvals and specifications. Consult the manufacturer for official OEM approval certificates.

TYPICAL PROPERTIES

Property	Unit	Test Method	Typical Value
Density (15°C)	g/cm³	ASTM D4052	**0,85 - 0,88**
Kinematic viscosity (100°C)	mm²/s	ASTM D445	**7.3**
Viscosity index	—	ASTM D2270	**Min. 165**
Flash point	°C	ASTM D92	**Min. 195**
Pour point	°C	ASTM D97	**Max. -42**

The values given are typical values and do not constitute a specification; minor variations may occur between production batches.

PACKAGING

20 L

EYLÜL OTO MADENİ YAĞ SANAYİ TİCARET LTD. ŞTİ. · AYDINLIKEVLER MAH. NAZMİ AKDENİZ CAD. NO:89/2B MİLAS/MUĞLA · Phone 0 507 368 63 20 · E-mail info@eylulticaret.com
Manufactured by: PARKİM GRES ENDÜSTRİYEL YAĞLAR SANAYİ VE TİCARET LTD. ŞTİ. · İnönü Mah., Gebze Plastikçiler OSB, 32. Sk. No: 11, 41400 Gebze / Kocaeli · Phone +90 262 206 01 01

STORAGE AND HANDLING RECOMMENDATIONS

- Store packages with lids tightly closed, in covered areas.
- Do not expose to direct sunlight or heat sources.
- Ambient temperature should not exceed 60°C. Do not stack more than two pallets on top of each other.
- Do not discharge used oil into sewers, soil or water; deliver it to an authorised waste oil collection point.
- Keep out of reach of children.

HEALTH, SAFETY AND ENVIRONMENT

For information on safe use, transport, storage and disposal, refer to the product Safety Data Sheet (SDS / MSDS).

EYLÜL OTO MADENİ YAĞ SANAYİ TİCARET LTD. ŞTİ. · AYDINLIKEVLER MAH. NAZMİ AKDENİZ CAD. NO:89/2B MİLAS/MUĞLA · Phone 0 507 368 63 20 · E-mail info@eylulticaret.com
Manufactured by: PARKİM GRES ENDÜSTRİYEL YAĞLAR SANAYİ VE TİCARET LTD. ŞTİ. · İnönü Mah., Gebze Plastikçiler OSB, 32. Sk. No: 11, 41400 Gebze / Kocaeli · Phone +90 262 206 01 01