ACTIVE KIRMIZI GRES

RED CALCIUM GREASE · NLGI 1 / 2 / 3

RED

PRODUCT DESCRIPTION

ACTIVE red grease is a water-resistant, multi-purpose calcium soap grease with a fibrous structure, produced with high quality base oils and special additives. It is suitable for low and medium speed bearings, low speed plain bearings and chassis applications where the operating temperature does not exceed 80°C.

APPLICATIONS AND KEY FEATURES

- Works under impact loads thanks to superior extreme pressure properties
- Extends bearing life by reducing fatigue and wear
- Adheres to metal surfaces thanks to its fibrous structure, protecting the metal and preventing waste
- Water resistant

TYPICAL PROPERTIES

Property	Unit	Test Method	Typical Value
Soap type	—	—	**Calcium (Ca)**
NLGI consistency grade	—	ASTM D217	**1 / 2 / 3**
Worked penetration (25°C)	0,1 mm	ASTM D217	**310-340 / 265-295 / 220-250**
Dropping point	°C	ASTM D566	**Min. 105**
Colour	—	Visual	**Red**

The values given are typical values and do not constitute a specification; minor variations may occur between production batches.

PACKAGING

0.9 kg · 3.6 kg · 15 kg · 185 kg

STORAGE AND HANDLING RECOMMENDATIONS

- Store packages with lids tightly closed, in covered areas.
- Do not expose to direct sunlight or heat sources.
- Ambient temperature should not exceed 60°C. Do not stack more than two pallets on top of each other.
- Do not discharge used oil into sewers, soil or water; deliver it to an authorised waste oil collection point.
- Keep out of reach of children.

HEALTH, SAFETY AND ENVIRONMENT

For information on safe use, transport, storage and disposal, refer to the product Safety Data Sheet (SDS / MSDS).

EYLÜL OTO MADENİ YAĞ SANAYİ TİCARET LTD. ŞTİ. · AYDINLIKEVLER MAH. NAZMİ AKDENİZ CAD. NO:89/2B MİLAS/MUĞLA · Phone 0 507 368 63 20 · E-mail info@eylulticaret.com
Manufactured by: PARKİM GRES ENDÜSTRİYEL YAĞLAR SANAYİ VE TİCARET LTD. ŞTİ. · İnönü Mah., Gebze Plastikçiler OSB, 32. Sk. No: 11, 41400 Gebze / Kocaeli · Phone +90 262 206 01 01