ACTIVE OIL 10W40 CI-4 SL

HEAVY DUTY TECHNOLOGY · DIESEL ENGINE OIL

10W-40

PRODUCT DESCRIPTION

It is an extra high performance, synthetic diesel engine oil designed to lubricate modern, high performance, low emission diesel engines used in demanding applications. This engine oil is designed using high-performance base oils that provide excellent low-temperature fluidity, high-temperature viscosity retention and evaporation control. Special additive packages have been used to extend the life and increase the efficiency of emission reduction systems such as Diesel Particulate Filter (DPF). The DPF meets the emission requirements required by Euro IV and Euro V.

APPLICATIONS AND KEY FEATURES

- Engines with EGR
- Euro VI engines
- Turbocharged engines
- Long drain intervals

PERFORMANCE LEVELS AND SPECIFICATIONS

- API SL, API CI-4, CJ-4
- ACEA E9-16
- E7-16, E6-16
- CAT ECF-3
- CES 20081-86
- DDC 93K222
- DEUTZ DQC IV-18 LA
- JASO DH-2
- MTU TYPE 3.1
- MACK EOS-4.5
- MAN M 3677, MB 228.51
- Renault RLD-3
- Volvo VDS-4.5
- IVECO ACEA 2016
- SCANIA LDF-4

Manufacturer statement: formulated with additives meeting the listed approvals and specifications. Consult the manufacturer for official OEM approval certificates.

TYPICAL PROPERTIES

Property	Unit	Test Method	Typical Value
Density (15°C)	g/cm³	ASTM D4052	**0.87 - 0.90**
Kinematic viscosity (100°C)	mm²/s	ASTM D445	**12.5 - 16.3**
Viscosity index	—	ASTM D2270	**Min. 150**
Flash point	°C	ASTM D92	**Min. 225**
Pour point	°C	ASTM D97	**Max. -36**

The values given are typical values and do not constitute a specification; minor variations may occur between production batches.

PACKAGING

20 L

STORAGE AND HANDLING RECOMMENDATIONS

- Store packages with lids tightly closed, in covered areas.
- Do not expose to direct sunlight or heat sources.
- Ambient temperature should not exceed 60°C. Do not stack more than two pallets on top of each other.
- Do not discharge used oil into sewers, soil or water; deliver it to an authorised waste oil collection point.
- Keep out of reach of children.

EYLÜL OTO MADENİ YAĞ SANAYİ TİCARET LTD. ŞTİ. · AYDINLIKEVLER MAH. NAZMİ AKDENİZ CAD. NO:89/2B MİLAS/MUĞLA · Phone 0 507 368 63 20 · E-mail info@eylulticaret.com
Manufactured by: PARKİM GRES ENDÜSTRİYEL YAĞLAR SANAYİ VE TİCARET LTD. ŞTİ. · İnönü Mah., Gebze Plastikçiler OSB, 32. Sk. No: 11, 41400 Gebze / Kocaeli · Phone +90 262 206 01 01

HEALTH, SAFETY AND ENVIRONMENT

For information on safe use, transport, storage and disposal, refer to the product Safety Data Sheet (SDS / MSDS).

EYLÜL OTO MADENİ YAĞ SANAYİ TİCARET LTD. ŞTİ. · AYDINLIKEVLER MAH. NAZMİ AKDENİZ CAD. NO:89/2B MİLAS/MUĞLA · Phone 0 507 368 63 20 · E-mail info@eylulticaret.com
Manufactured by: PARKİM GRES ENDÜSTRİYEL YAĞLAR SANAYİ VE TİCARET LTD. ŞTİ. · İnönü Mah., Gebze Plastikçiler OSB, 32. Sk. No: 11, 41400 Gebze / Kocaeli · Phone +90 262 206 01 01