ACTIVE OIL 10W40 MOLYGEN

MOLY-GEN TECHNOLOGY · LOW FRICTION ENGINE OIL

10W-40

PRODUCT DESCRIPTION

A high-performance, low-friction, all-season fully synthetic engine oil. Special base oils, advanced additive technology and a friction-reducing additive provide high shear stability, prevent deposits, reduce friction losses and give optimum wear protection. Remains stable over long drain intervals and under extreme operating conditions, with instant lubrication after cold start. For modern gasoline and diesel passenger car engines with or without turbocharger; tested with turbochargers and catalytic converters. Consult the vehicle handbook before use.

APPLICATIONS AND KEY FEATURES

- Fuel economy
- Gasoline engines
- Diesel engines
- Turbocharged engines

PERFORMANCE LEVELS AND SPECIFICATIONS

- ACEA A3 / B4
- API SN
- MB 229.3
- VW 501 01 / 502 00 / 505 00
- RENAULT RN0700 / RN0710
- PSA B71 2300
- FIAT 9.55535-G2

Performance levels stated on the product label under “Meets & Exceeds”. Consult the manufacturer for official OEM approval certificates.

TYPICAL PROPERTIES

Property	Unit	Test Method	Typical Value
Density (15°C)	g/cm³	DIN 51757	**0.865**
Kinematic viscosity (40°C)	mm²/s	ASTM D7042	**95.0**
Kinematic viscosity (100°C)	mm²/s	ASTM D7042	**14.2**
Viscosity index	—	DIN ISO 2909	**155**
HTHS viscosity (150°C)	mPa·s	ASTM D5481	**Min, 3.5**
Flash point	°C	DIN ISO 2592	**220**
Pour point	°C	DIN ISO 3016	**-39**
Total base number (TBN)	mg KOH/g	DIN ISO 3771	**11**

The values given are typical values and do not constitute a specification; minor variations may occur between production batches.

PACKAGING

4 L

STORAGE AND HANDLING RECOMMENDATIONS

- Store packages with lids tightly closed, in covered areas.
- Do not expose to direct sunlight or heat sources.
- Ambient temperature should not exceed 60°C. Do not stack more than two pallets on top of each other.
- Do not discharge used oil into sewers, soil or water; deliver it to an authorised waste oil collection point.
- Keep out of reach of children.

EYLÜL OTO MADENİ YAĞ SANAYİ TİCARET LTD. ŞTİ. · AYDINLIKEVLER MAH. NAZMİ AKDENİZ CAD. NO:89/2B MİLAS/MUĞLA · Phone 0 507 368 63 20 · E-mail info@eylulticaret.com
Manufactured by: PARKİM GRES ENDÜSTRİYEL YAĞLAR SANAYİ VE TİCARET LTD. ŞTİ. · İnönü Mah., Gebze Plastikçiler OSB, 32. Sk. No: 11, 41400 Gebze / Kocaeli · Phone +90 262 206 01 01

HEALTH, SAFETY AND ENVIRONMENT

For information on safe use, transport, storage and disposal, refer to the product Safety Data Sheet (SDS / MSDS).

EYLÜL OTO MADENİ YAĞ SANAYİ TİCARET LTD. ŞTİ. · AYDINLIKEVLER MAH. NAZMİ AKDENİZ CAD. NO:89/2B MİLAS/MUĞLA · Phone 0 507 368 63 20 · E-mail info@eylulticaret.com
Manufactured by: PARKİM GRES ENDÜSTRİYEL YAĞLAR SANAYİ VE TİCARET LTD. ŞTİ. · İnönü Mah., Gebze Plastikçiler OSB, 32. Sk. No: 11, 41400 Gebze / Kocaeli · Phone +90 262 206 01 01