ACTIVE OIL 15W40 CI-4 SL

HEAVY DUTY TECHNOLOGY · DIESEL ENGINE OIL

15W-40

PRODUCT DESCRIPTION

ACTIVE OIL 15W40 CI-4 SL reinforced with superior quality base oils and extra additives, developed to be used in new generation diesel engines operating under severe conditions . It is recommended for use in vehicles with diesel turbocharged engines such as trucks, buses and construction equipment.

APPLICATIONS AND KEY FEATURES

- Engines with EGR
- Compatible with SCR systems
- Euro V engines
- Turbocharged engines

PERFORMANCE LEVELS AND SPECIFICATIONS

- API CI-4/SL
- ACEA E7
- DEUTZ DQC III-10
- MACK EO-N
- MB-APPROVAL 228.3
- RENAULT VI RLD-2
- VOLVO VDS-3 PERFORMANCES
- CAT ECF-2
- CUMMINS CES 20078/77/76
- GLOBAL DHD-1
- MAN M 3275-1
- MTU DDC TYPE 2

Manufacturer statement: formulated with additives meeting the listed approvals and specifications. Consult the manufacturer for official OEM approval certificates.

TYPICAL PROPERTIES

Property	Unit	Test Method	Typical Value
Density (15°C)	g/cm³	ASTM D4052	**0.87 - 0.90**
Kinematic viscosity (100°C)	mm²/s	ASTM D445	**12.5 - 16.3**
Viscosity index	—	ASTM D2270	**Min. 120**
Flash point	°C	ASTM D92	**Min. 230**
Pour point	°C	ASTM D97	**Max. -27**

The values given are typical values and do not constitute a specification; minor variations may occur between production batches.

PACKAGING

20 L

STORAGE AND HANDLING RECOMMENDATIONS

- Store packages with lids tightly closed, in covered areas.
- Do not expose to direct sunlight or heat sources.
- Ambient temperature should not exceed 60°C. Do not stack more than two pallets on top of each other.
- Do not discharge used oil into sewers, soil or water; deliver it to an authorised waste oil collection point.
- Keep out of reach of children.

HEALTH, SAFETY AND ENVIRONMENT

For information on safe use, transport, storage and disposal, refer to the product Safety Data Sheet (SDS / MSDS).

EYLÜL OTO MADENİ YAĞ SANAYİ TİCARET LTD. ŞTİ. · AYDINLIKEVLER MAH. NAZMİ AKDENİZ CAD. NO:89/2B MİLAS/MUĞLA · Phone 0 507 368 63 20 · E-mail info@eylulticaret.com
Manufactured by: PARKİM GRES ENDÜSTRİYEL YAĞLAR SANAYİ VE TİCARET LTD. ŞTİ. · İnönü Mah., Gebze Plastikçiler OSB, 32. Sk. No: 11, 41400 Gebze / Kocaeli · Phone +90 262 206 01 01