ACTIVE OIL 5W30 MOLYGEN

MOLY-GEN TECHNOLOGY · LOW FRICTION ENGINE OIL

5W-30

PRODUCT DESCRIPTION

A low-friction, all-season fully synthetic engine oil. Advanced wear protection technology and a high performance reserve, with strong dirt suspending and cleaning capacity for optimum engine cleanliness. Saves fuel and supports a long service life of the diesel particulate filter (DPF) and the engine. For gasoline and diesel engines including common rail, especially vehicles with DPF; tested with turbochargers and catalytic converters. Instant lubrication after cold start, high shear stability and optimum oil pressure under all conditions. Consult the vehicle handbook before use.

APPLICATIONS AND KEY FEATURES

- Fuel economy
- Compatible with SCR systems
- DPF compatible
- Start-stop systems

PERFORMANCE LEVELS AND SPECIFICATIONS

- ACEA C2 / C3
- API SN
- BMW LONGLIFE-04 (UP TO 2018)
- FIAT 9.55535-S3
- FORD WSS-M2C917-A
- GM dexos2
- MB 229.31 / 229.51 / 229.52
- OPEL GM-LL-A-025 / GM-LL-B-025
- VW 505 00 / 505 01
- RECOMMENDED FOR: GWM, HAVAL, HYUNDAI, KIA, WULING

Performance levels stated on the product label under “Meets & Exceeds”. Consult the manufacturer for official OEM approval certificates.

TYPICAL PROPERTIES

Property	Unit	Test Method	Typical Value
Density (15°C)	g/cm³	DIN 51757	**0.850**
Kinematic viscosity (40°C)	mm²/s	ASTM D7042	**71.0**
Kinematic viscosity (100°C)	mm²/s	ASTM D7042	**12.2**
Viscosity index	—	DIN ISO 2909	**170**
HTHS viscosity (150°C)	mPa·s	ASTM D5481	**Min, 3.5**
Flash point	°C	DIN ISO 2592	**220**
Pour point	°C	DIN ISO 3016	**-39**
Total base number (TBN)	mg KOH/g	DIN ISO 3771	**7.5**

The values given are typical values and do not constitute a specification; minor variations may occur between production batches.

PACKAGING

4 L · 5 L

STORAGE AND HANDLING RECOMMENDATIONS

- Store packages with lids tightly closed, in covered areas.
- Do not expose to direct sunlight or heat sources.
- Ambient temperature should not exceed 60°C. Do not stack more than two pallets on top of each other.
- Do not discharge used oil into sewers, soil or water; deliver it to an authorised waste oil collection point.
- Keep out of reach of children.

EYLÜL OTO MADENİ YAĞ SANAYİ TİCARET LTD. ŞTİ. · AYDINLIKEVLER MAH. NAZMİ AKDENİZ CAD. NO:89/2B MİLAS/MUĞLA · Phone 0 507 368 63 20 · E-mail info@eylulticaret.com
Manufactured by: PARKİM GRES ENDÜSTRİYEL YAĞLAR SANAYİ VE TİCARET LTD. ŞTİ. · İnönü Mah., Gebze Plastikçiler OSB, 32. Sk. No: 11, 41400 Gebze / Kocaeli · Phone +90 262 206 01 01

HEALTH, SAFETY AND ENVIRONMENT

For information on safe use, transport, storage and disposal, refer to the product Safety Data Sheet (SDS / MSDS).

EYLÜL OTO MADENİ YAĞ SANAYİ TİCARET LTD. ŞTİ. · AYDINLIKEVLER MAH. NAZMİ AKDENİZ CAD. NO:89/2B MİLAS/MUĞLA · Phone 0 507 368 63 20 · E-mail info@eylulticaret.com
Manufactured by: PARKİM GRES ENDÜSTRİYEL YAĞLAR SANAYİ VE TİCARET LTD. ŞTİ. · İnönü Mah., Gebze Plastikçiler OSB, 32. Sk. No: 11, 41400 Gebze / Kocaeli · Phone +90 262 206 01 01