# ACTIVE ATF DEXRON III SARI

DEXRON III TRANSMISSION OIL

ATF III

## PRODUCT DESCRIPTION

ACTIVE ATF DEXRON III is an automatic transmission fluid (ATF) recommended for many passenger car and commercial vehicle automatic transmissions. Its stable viscosity and zinc-free, friction-reducing additive technology give excellent grip and protection for years. Also suitable for power steering, hydraulic applications and some manual transmissions where ATF is specified.

## APPLICATIONS AND KEY FEATURES

- Dexron Iii
- Mercon

## PERFORMANCE LEVELS AND SPECIFICATIONS

- GM DEXRON III H
- FORD MERCON
- ALLISON C4
- VOLVO 97341
- TES 389
- MAN 339 TYPE V1 / Z1
- MB 236.1 / 236.9
- VOITH 55.6335
- ZF TE-ML 03D / 04D / 14A / 17C

*Performance levels stated on the product label under “Meets & Exceeds”. Consult the manufacturer for official OEM approval certificates.*

## TYPICAL PROPERTIES

| Property | Unit | Test Method | Typical Value |
|---|---|---|---|
| **Density (15°C)** | g/cm³ | — | *Manufacturer confirmation required* |
| **Kinematic viscosity (40°C)** | mm²/s | — | *Manufacturer confirmation required* |
| **Kinematic viscosity (100°C)** | mm²/s | ASTM D445 | **7.2 - 9.4** |
| **Viscosity index** | — | ASTM D2270 | **Min. 150** |
| **Flash point** | °C | ASTM D92 | **Min. 215** |
| **Pour point** | °C | ASTM D97 | **Max. -36** |

*The values given are typical values and do not constitute a specification; minor variations may occur between production batches.*

## PACKAGING

**1 L · 20 L · 200 L**

## STORAGE AND HANDLING RECOMMENDATIONS

- Store packages with lids tightly closed, in covered areas.
- Do not expose to direct sunlight or heat sources.
- Ambient temperature should not exceed 60°C. Do not stack more than two pallets on top of each other.
- Do not discharge used oil into sewers, soil or water; deliver it to an authorised waste oil collection point.
- Keep out of reach of children.

## HEALTH, SAFETY AND ENVIRONMENT

For information on safe use, transport, storage and disposal, refer to the product Safety Data Sheet (SDS / MSDS).



**EYLÜL OTO MADENİ YAĞ SANAYİ TİCARET LTD. ŞTİ.** · AYDINLIKEVLER MAH. NAZMİ AKDENİZ CAD. NO:89/2B MİLAS/MUĞLA · Phone 0 507 368 63 20 · E-mail info@eylulticaret.com
**Manufactured by: PARKİM GRES ENDÜSTRİYEL YAĞLAR SANAYİ VE TİCARET LTD. ŞTİ.** · İnönü Mah., Gebze Plastikçiler OSB, 32. Sk. No: 11, 41400 Gebze / Kocaeli · Phone +90 262 206 01 01

**DRAFT — This document must be verified against manufacturer data before publication, and the SDS must be approved by a competent (certified) Safety Data Sheet preparer.**