ACTIVE HYDRAULIC HLP 37

ANTI-WEAR HYDRAULIC OIL

HLP 37

PRODUCT DESCRIPTION

ACTIVE HYDRAULIC HLP 37 is a hydraulic system oil formulated from high-quality base oils with oxidation, wear and rust inhibitors. Used in industrial systems and mobile hydraulics. Keeps its properties at high temperature and resists corrosion, foaming and sludge.

APPLICATIONS AND KEY FEATURES

- DIN 51524-2 HLP class
- Anti-wear
- Anti-rust

PERFORMANCE LEVELS AND SPECIFICATIONS

- DIN 51524 PART 2
- DENISON HF-0 / HF-1 / HF-2
- CINCINNATI MACHINE P-68 / P-69 / P-70
- U.S. STEEL 127 / 136
- BOSCH REXROTH
- EATON VICKERS M-2950-S / I-286-S
- AFNOR NF E 48-690 / 48-691
- GM LS-2, JCMAS HK, SAE MS1004

Performance levels stated on the product label under “Meets & Exceeds”. Consult the manufacturer for official OEM approval certificates.

TYPICAL PROPERTIES

Property	Unit	Test Method	Typical Value
ISO viscosity grade	—	—	**ISO VG 37**
Density (15°C)	g/cm³	—	*Manufacturer confirmation required*
Kinematic viscosity (40°C)	mm²/s	ASTM D445	**35.2 - 41.4**
Kinematic viscosity (100°C)	mm²/s	—	*Manufacturer confirmation required*
Viscosity index	—	ASTM D2270	**Min. 95**
Flash point	°C	ASTM D92	**Min. 210**
Pour point	°C	ASTM D97	**Max. -25**

The values given are typical values and do not constitute a specification; minor variations may occur between production batches.

PACKAGING

20 L · 200 L

STORAGE AND HANDLING RECOMMENDATIONS

- Store packages with lids tightly closed, in covered areas.
- Do not expose to direct sunlight or heat sources.
- Ambient temperature should not exceed 60°C. Do not stack more than two pallets on top of each other.
- Do not discharge used oil into sewers, soil or water; deliver it to an authorised waste oil collection point.
- Keep out of reach of children.

HEALTH, SAFETY AND ENVIRONMENT

For information on safe use, transport, storage and disposal, refer to the product Safety Data Sheet (SDS / MSDS).

EYLÜL OTO MADENİ YAĞ SANAYİ TİCARET LTD. ŞTİ. · AYDINLIKEVLER MAH. NAZMİ AKDENİZ CAD. NO:89/2B MİLAS/MUĞLA · Phone 0 507 368 63 20 · E-mail info@eylulticaret.com
Manufactured by: PARKİM GRES ENDÜSTRİYEL YAĞLAR SANAYİ VE TİCARET LTD. ŞTİ. · İnönü Mah., Gebze Plastikçiler OSB, 32. Sk. No: 11, 41400 Gebze / Kocaeli · Phone +90 262 206 01 01

DRAFT — This document must be verified against manufacturer data before publication, and the SDS must be approved by a competent (certified) Safety Data Sheet preparer.