ACTIVE TRACTOR FLUID 422

UTTO / STOU TRACTOR TRANSMISSION OIL

422

PRODUCT DESCRIPTION

ACTIVE TRACTOR FLUID 422 is an extra-high-performance multi-purpose tractor oil designed to meet the requirements of hydraulic and transmission component manufacturers. Used in transmissions, hydraulics, wet brakes and axles of agricultural and construction machinery; prevents chatter and noise in wet brakes.

APPLICATIONS AND KEY FEATURES

- Utto
- Stou
- Wet Brake

PERFORMANCE LEVELS AND SPECIFICATIONS

- UTTO: API GL-4
- MASSEY FERGUSON CMS M1143 / M1135
- CNH MAT 3525 / 3526
- ALLISON C4
- ZF TE-ML 07B / 06D / 06C / 06B
- JOHN DEERE J20C
- FORD M2C 134D
- STOU: API CF-4 / SF
- MASSEY FERGUSON CMS M1144 / M1139
- JOHN DEERE J27
- NEW HOLLAND NH 030C / NH 024C
- ACEA E2 / E3, MB 228.3
- FORD M2C 159B/C

Performance levels stated on the product label under “Meets & Exceeds”. Consult the manufacturer for official OEM approval certificates.

TYPICAL PROPERTIES

Property	Unit	Test Method	Typical Value
ISO viscosity grade	—	—	*Manufacturer confirmation required*
Density (15°C)	g/cm³	—	*Manufacturer confirmation required*
Kinematic viscosity (40°C)	mm²/s	—	*Manufacturer confirmation required*
Kinematic viscosity (100°C)	mm²/s	ASTM D445	**9.3 - 12.5**
Viscosity index	—	ASTM D2270	**Min. 140**
Flash point	°C	ASTM D92	**Min. 220**
Pour point	°C	ASTM D97	**Max. -36**

The values given are typical values and do not constitute a specification; minor variations may occur between production batches.

PACKAGING

20 L · 200 L

STORAGE AND HANDLING RECOMMENDATIONS

- Store packages with lids tightly closed, in covered areas.
- Do not expose to direct sunlight or heat sources.
- Ambient temperature should not exceed 60°C. Do not stack more than two pallets on top of each other.
- Do not discharge used oil into sewers, soil or water; deliver it to an authorised waste oil collection point.
- Keep out of reach of children.

EYLÜL OTO MADENİ YAĞ SANAYİ TİCARET LTD. ŞTİ. · AYDINLIKEVLER MAH. NAZMİ AKDENİZ CAD. NO:89/2B MİLAS/MUĞLA · Phone 0 507 368 63 20 · E-mail info@eylulticaret.com
Manufactured by: PARKİM GRES ENDÜSTRİYEL YAĞLAR SANAYİ VE TİCARET LTD. ŞTİ. · İnönü Mah., Gebze Plastikçiler OSB, 32. Sk. No: 11, 41400 Gebze / Kocaeli · Phone +90 262 206 01 01

DRAFT — This document must be verified against manufacturer data before publication, and the SDS must be approved by a competent (certified) Safety Data Sheet preparer.

HEALTH, SAFETY AND ENVIRONMENT

For information on safe use, transport, storage and disposal, refer to the product Safety Data Sheet (SDS / MSDS).

EYLÜL OTO MADENİ YAĞ SANAYİ TİCARET LTD. ŞTİ. · AYDINLIKEVLER MAH. NAZMİ AKDENİZ CAD. NO:89/2B MİLAS/MUĞLA · Phone 0 507 368 63 20 · E-mail info@eylulticaret.com
Manufactured by: PARKİM GRES ENDÜSTRİYEL YAĞLAR SANAYİ VE TİCARET LTD. ŞTİ. · İnönü Mah., Gebze Plastikçiler OSB, 32. Sk. No: 11, 41400 Gebze / Kocaeli · Phone +90 262 206 01 01

DRAFT — This document must be verified against manufacturer data before publication, and the SDS must be approved by a competent (certified) Safety Data Sheet preparer.